

Varnostni list**DILUENTE ADW**

Varnostni list z dne 12/06/2023 revizija 1

Pozor: oštevilčenje se znova začne od 1.

ODDELEK 1: Identifikacija snovi/zmesi in družbe/podjetja**1.1 Identifikator izdelka**

Identifikacija pripravka:

Komerčno ime: DILUENTE ADW

Komerčna koda: 583K

UFI: D2M1-00XS-S00R-AKV1

1.2 Pomembne identificirane uporabe snovi ali zmesi in odsvetovane uporabe

Priporočena uporaba: Razredčilo

1.3 Podrobnosti o dobavitelju varnostnega lista

Dobavitelj FASSA Srl

Via Lazzaris, 3 - 31027 Spresiano (TV) - ITALY

Tel. +39 0422 7222

Fax +39 0422 887509

Odgovorni: laboratorio.spresiano@fassabortolo.it

1.4 Telefonska številka za nujne primere

112 - Center za obveščanje (na voljo 24 ur)

ODDELEK 2: Določitev nevarnosti**2.1 Razvrstitev snovi ali zmesi****Uredba (ES) št. 1272/2008 (CLP)**

Flam. Liq. 2	Lahko vnetljiva tekočina in hlapi.
Eye Irrit. 2	Povzroča hudo draženje oči.
STOT SE 3	Lahko povzroči zaspanost ali omotico.

Nevarnosti fizikalno-kemijskih lastnosti za zdravje ljudi in za okolje:

Ni drugih tveganj

2.2 Elementi etikete**Uredba (ES) št. 1272/2008 (CLP)****Piktogrami za nevarnost in Opozorilna beseda**

Nevarno

Stavki o nevarnosti

H225	Lahko vnetljiva tekočina in hlapi.
H319	Povzroča hudo draženje oči.
H336	Lahko povzroči zaspanost ali omotico.

Previdnostni stavki

P210	Hraniti ločeno od vročine, vročih površin, isker, odprtega ognja in drugih virov vžiga. Kajenje prepovedano.
P233	Hraniti v tesno zaprti posodi.
P261	Ne vdihavati dima/plina/meglvice/hlapov/razpršila.
P280	Nadenite si zaščitne rokavice in zaščitite oči/obraz.
P312	Ob slabem počutju pokličite CENTER ZA ZASTRUPITVE/zdravnika.
P370+P378	Ob požaru: gasite z gasilnim aparatom na prah.
P403+P235	Hraniti na dobro prezračevanem mestu. Hraniti na hladnem.

Posebne oznake:

EUH066 Ponavljajoča izpostavljenost lahko povzroči nastanek suhe ali razpokane kože.

Vsebuje:

etil acetat
n-butil acetat

Posebne določbe v skladu s Prilogo XVII uredbe REACH in poznejše spremembe:

Nobeden

2.3 Druge nevarnosti

Ni snovi PBT, vPvB ali endokrinih motilcev v koncentraciji > = 0,1%.

Ni drugih tveganj

ODDELEK 3: Sestava/podatki o sestavinah

3.1 Snovi

ni znano

3.2 Zmesi

Identifikacija pripravka: DILUENTE ADW

Nevarne sestavine, skladno z Uredbo CLP in njeno razvrstitvijo:

Količina	Ime	Ident. št.	Razvrstitev	Registracijska številka
≥ 80%	etil acetat	CAS:141-78-6 EC:205-500-4 Index:607-022-00-5	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	01-2119475103-46-xxxx
≥5 - <10 %	n-butil acetat	CAS:123-86-4 EC:204-658-1 Index:607-025-00-1	Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	01-2119485493-29-xxxx

ODDELEK 4: Ukrepi za prvo pomoč

4.1 Opis ukrepov za prvo pomoč

V primeru stika s kožo:

Kontaminirana oblačila takoj slecite in jih na varen način odstranite.
V primeru stika s proizvodom in tudi v primeru suma morebitnega stika, dele telesa takoj umijte z veliko količino tekoče vode in milom.
Umijte celotno telo (tuširanje ali kopel).

V primeru stika z očmi:

V primeru stika z očmi dovolj dolgo in z odprtimi očesnimi vekami izpirajte z obilo vode, nato poiščite pomoč zdravnika oftalmologa.
Poškodovano oko zaščitite.

V primeru zaužitja:

Po zaužitju ne izzivati bruhanja, takoj poiskati zdravniško pomoč in pokazati varnostni list in nalepko.

V primeru vdihavanja:

Prizadeto osebo umaknite na svež zrak in pustite počivati na toplem.

4.2 Najpomembnejši simptomi in učinki, akutni in zapozneli

Simptomi in učinki so taki, kot je pričakovano glede na nevarnosti, kar je prikazano v 2. razdelku.

4.3 Navedba kakršne koli takojšnje medicinske oskrbe in posebnega zdravljenja

V primeru nesreče ali slabega počutja takoj poiščite zdravniško pomoč (če je mogoče, pokažite navodila za uporabo ali varnostni list).

ODDELEK 5: Protipožarni ukrepi

5.1 Sredstva za gašenje

Ustrezna sredstva za gašenje:

Ob požaru: gasite z gasilnim aparatom na prah.
CO2, gasilni aparat na prah, pena, pršenje z vodo.

Sredstva za gašenje, ki se jih iz varnostnih razlogov ne sme uporabljati:

Vodni curki

5.2 Posebne nevarnosti v zvezi s snovjo ali zmesjo

Pri gorenju nastajajo težki dimni plini.
Ne vdihavati pline, ki nastanejo pri eksploziji in/ali gorenju (ogljikov monoksid in ogljikov dioksid, dušikovi oksidi).
Hlapi lahko tvorijo eksplozivne zmesi z zrakom.

5.3 Nasvet za gasilce

Uporabiti ustrezne dihalne naprave.

Ločeno zberite kontaminirano vodo, uporabljeno za gašenje požara. Ne je izpustiti v kanalizacijo.

Če je to varno izvedljivo, nepoškodovane vsebnike umaknite iz neposredno ogroženega območja.

ODDELEK 6: Ukrepi o nenamernih izpustih

6.1 Osebn varnostni ukrepi, zaščitna oprema in postopki v sili

Nosite osebno varovalno opremo.

Odstranite vse vire vžiga.

Osebe umaknite na varno mesto.

Glejte v točki 7 in 8 navedene zaščitne ukrepe.

6.2 Okoljevarstveni ukrepi

Preprečite vstop v tla/podtalnico. Preprečite razlitje v površinske vode ali v kanalizacijo.

V primeru puščanja plina ali razlitja v vodne tokove, tla ali kanalizacijo obvestite pristojne organe.

6.3 Metode in materiali za zadrževanje in čiščenje

Za zbiranje primeren material: inerten vpojni materiali (npr. pesek, vermikulit).

Kontaminirano vodo za pranje shranite in odstranite.

6.4 Sklicevanje na druge oddelke

Glejte tudi naslova 8 in 13

ODDELEK 7: Ravnanje in skladiščenje

7.1 Varnostni ukrepi za varno ravnanje

Preprečite stik s kožo in očmi, vdihavanje hlapov in megle.

Prazne vsebnike ne uporabite dokler niso očiščeni.

Pred postopki prenosa se prepričajte, da v vsebnikih ni ostankov nezdružljivih materialov.

Nasveti o splošni higieni dela:

Kontaminirana oblačila se mora pred vstopom v jedilnico zamenjati.

Med delom ne jejte in ne pijte.

Glejte tudi naslov 8 o priporočeni varovalni opremini.

7.2 Pogoji za varno skladiščenje, vključno z nezdružljivostjo

Posode hranite tesno zaprte na hladnem in dobro prezračevanem mestu proč od virov toplote.

Hranite daleč od prostih plamenov, isker in virov toplote. Izogibajte se neposredni izpostavitvi soncu.

Hranite stran od hrane, pijač in krme.

Inkompaktibilne snovi:

Glejte točko 10.5

Navodila za prostore:

Hladni in primerno zračeni.

7.3 Posebne končne uporabe

Priporočila

Glejte točko 1.2

Specifične rešitve za industrijski sektor

Nobena posebna uporaba

ODDELEK 8: Nadzor izpostavljenosti/osebna zaščita

8.1 Parametri nadzora

Seznam sestavin z OEL vrednostmi

	Način izpostavljenosti na delovnem mestu	Država	Dolgotrajna mg/m³	Dolgotrajne jša ppm	Kratkotrajna a mg/m³	Kratkotrajna a ppm	Opomba
etil acetat CAS: 141-78-6	ACGIH			400			URT and eye irr
	EU		734	200	1468	400	
	MAK	AUSTRIA	734.000	200	1468.000	400	
	VLEP	BELGIUM	734.000	200	1468.000	400	
	VLEP	FRANCE	734.000	200	1468.000	400	
	AGW	GERMANY	730.000	200.000	1460.000	400	

n-butil acetat CAS: 123-86-4	MAK	GERMANY	750.000	200.000	1500.000	400.000	Eye and URT irr
	ÁK	HUNGARY	1400		1400		
	VLEP	ITALY	734	200.000	1468	400.000	
	NDS	POLAND	734.000		1468.000		
	VLEP	ROMANIA	400.000	111.000	500.000	139.000	
	VLA	SPAIN	734.000	200.000	1460.000	400.000	
	SUVA	SWITZERLAN D	730.000	200.000	1470.000	400.000	
	WEL	U.K.	730.000	200.000	1460.000	400.000	
	VLE	PORTUGAL	734.000	200.000	1468.000	400.000	
	GVI	CROATIA	734.000	200.000	1468.000	400.000	
	MV	SLOVENIA	734.000	200.000	1468.000	400.000	
	TLV	CZECHIA	700.000	191.100	900.000	245.700	
	IPRV	LITHUANIA	500.000	150.000	1100.000	300.000	
	TLV	BULGARIA	734.000	200.000	1468.000	400.000	
	ACGIH			50		150	
	EU		241	50	723	150	
	MAK	AUSTRIA	480	100	480.000	100.000	
	VLEP	BELGIUM	238.000	50.000	712.000	150.000	
	VLEP	FRANCE	710.000	150	940.000	200	
	AGW	GERMANY	300.000	62.000	600.000	124.000	
	MAK	GERMANY	480.000	100.000	960.000	200	
	ÁK	HUNGARY	950		950		
	NDS	POLAND	240		720		
	VLEP	ROMANIA	715.000	150.000	950.000	200.000	
	VLA	SPAIN	724.000	150.000	965.000	200.000	
	SUVA	SWITZERLAN D	240.000	50.000	720.000	150.000	
	WEL	U.K.	724.000	150.000	966.000	200.000	
	GVI	CROATIA	724.000	150.000	966.000	200.000	
	MV	SLOVENIA	300.000	62.000	600.000	124.000	
	TLV	CZECHIA	241.000		723.000		
	TLV	BULGARIA	710.000		950.000		

Mejna vrednost izpostavljenosti po PNEC

	PNEC Omejit e	Način izpostavitve	Pogostost izpostavitve	Opombe
etil acetat CAS: 141-78-6	0.024 mg/l	Morska voda		
	0.24 mg/l	Sladka voda		
	0.115 mg/kg	Morski sedimenti		
	1.15 mg/kg	Sladkovodni sedimenti		
	650 mg/l	Mikroorganizmi v čistilnih napravah (STP)		
	0.148 mg/kg	Tla (kmetijska)		
n-butil acetat CAS: 123-86-4	0.018 mg/l	Morska voda		
	0.18 mg/l	Sladka voda		

0.098 mg/kg	Morski sedimenti
0.981 mg/kg	Sladkovodni sedimenti
35.6 mg/l	Mikroorganizmi v čistilnih napravah (STP)
0.09 mg/kg	Tla (kmetijska)

Izpeljane vrednosti brez učinka. (DNEL)

	Industrijski delavec	Strokovni delavec	Uporabnik	Način izpostavitve	Pogostost izpostavitve	Opombe
etil acetat CAS: 141-78-6		734 mg/m3	367 mg/m3	Z vdihanje m, človek	Dolgotrajna, sistemski učinek	
		734 mg/m3	367 mg/m3	Z vdihanje m, človek	Dolgotrajna, lokalni učinek	
		1468 mg/m3	734 mg/m3	Z vdihanje m, človek	Kratkotrajna, sistemski učinek	
		1468 mg/m3	734 mg/m3	Z vdihanje m, človek	Kratkotrajna, lokalni učinek	
		63 mg/kg	37 mg/kg	Dermalno, človek	Dolgotrajna, sistemski učinek	
n-butil acetat CAS: 123-86-4			4.5 mg/kg	Oralno, človek	Dolgotrajna, sistemski učinek	
		300 mg/m3	35.7 mg/m3	Z vdihanje m, človek	Dolgotrajna, sistemski učinek	
		600 mg/m3	300 mg/m3	Z vdihanje m, človek	Kratkotrajna, sistemski učinek	
		300 mg/m3	35.7 mg/m3	Z vdihanje m, človek	Dolgotrajna, lokalni učinek	
		600 mg/m3	300 mg/m3	Z vdihanje m, človek	Kratkotrajna, lokalni učinek	
		11 mg/kg	6 mg/kg	Dermalno, človek	Dolgotrajna, sistemski učinek	
		11 mg/kg	6 mg/kg	Dermalno, človek	Kratkotrajna, sistemski učinek	
			2 mg/kg	Oralno, človek	Kratkotrajna, sistemski učinek	
			2 mg/kg	Oralno, človek	Dolgotrajna, sistemski učinek	

8.2 Nadzor izpostavljenosti

Poskrbite za ustrezno prezračevanje. Kadar je to izvedljivo, je to mogoče doseči z uporabo nadomestnega prezračevanja in dobrim splošnim vsesavanjem.

Zaščita oči:

Očala s stranskimi varovali (EN 166).

Zaščita kože:

Osebjem naj nosi antistatična oblačila iz naravnih ali sintetičnih vlaken, odpornih na visoke temperature.

Zaščita rok:

Ni materiala ali kombinacije materialov za rokavice, ki bi lahko zagotovili neomejeno odpornost na katero koli kombinacijo kemikalij

ali proizvodov.

Za daljše ali večkratno rokovanje uporabite rokavice, odporne na kemikalije.

Ustrezne rokavice tipa (EN 374/EN 16523); FKM (Fluórkaučuk): debelina ≥ 0.4 mm; permeacijski čas ≥ 480 min.; NBR (Nitrilkaučuk): debelina ≥ 0.4 mm; permeacijski čas ≥ 480 min.

Izbira primernih rokavic ni odvisna samo od materiala, temveč tudi od drugih kakovostnih lastnosti, ki se razlikujejo od enega do drugega proizvajalca, in od načinov ter časov uporabe mešanice.

Zaščita dihalnih poti:

Če so delavci izpostavljeni koncentracijam nad mejnimi vrednostmi izpostavljenosti, morajo uporabljati primerne, certificirane dihalne aparate.

Kombinirana filtrirna naprava (EN 14387): maska s filtrom A-P2.

Nadzor izpostavljenosti okolja:

Glejte točko 6.2

Higienski in tehnični ukrepi

Glejte poglavje 7.

ODDELEK 9: Fizikalne in kemijske lastnosti

9.1 Podatki o osnovnih fizikalnih in kemijskih lastnostih

Izgled: Tekoče

Barva: brezbarven

Vonj: saden

Tališče/ledišče: N.D.

Točka začetka vretja in interval vretja: > 77 °C (171 °F)

Vnetljivost: Proizvod je razvrščen Flam. Liq. 2 H225

Zgornja/spodnja meja vnetljivosti ali eksplozivnosti: N.D.

Plamenišče: < 23 °C

Temperatura samovžiga: N.D.

Temperatura razgradnje: N.D.

pH: ni znano (Ne pride v poštev zaradi narave proizvoda)

Kinematična viskoznost: ni znano

Gustota: 0,9 kg/l (Interna metoda)

Gostota hlapov: 3,04

Parni tlak: N.D.

Topnost v vodi: ni znano

Topnost v olju: ni znano

Porazdelitveni koeficient (n-oktanol/voda): ni znano

Lastnosti delcev:

Velikost delcev: ni znano

9.2 Drugi podatki

Prevodnost: N.D.

Eksplozivne lastnosti: ni znano

Oksidativne lastnosti: ni znano

Hitrost izparevanja: ni znano

ODDELEK 10: Obstočnost in reaktivnost

10.1 Reaktivnost

Stabilna v normalnih pogojih

10.2 Kemijska stabilnost

Stabilna v normalnih pogojih

10.3 Možnost poteka nevarnih reakcij

Zaradi toplote ali v primeru požara se lahko sprostijo ogljikovi oksidi in hlapi, ki lahko škodujejo zdravju.

Hraniti ločeno od oksidantov, močno alkalnih in močno kislih snovi, da se izognete eksotermnim reakcijam.

Hlapi lahko tvorijo eksplozivne zmesi z zrakom.

10.4 Pogoji, ki se jim je treba izogniti

Izogibajte se bližine toplotnih virov.

10.5 Nezdružljivi materiali

Izogibati se stiku z oksidativnimi materiali. Proizvod lahko zagori.

Glejte točko 10.3

10.6 Nevarni produkti razgradnje

V primeru pravilnega skladiščenja in ravnanja ne pride do razvoja nevarnih produktov razgradnje.

Glejte točko 5.2

ODDELEK 11: Toksikološki podatki

11.1 Podatki o razredih nevarnosti, kakor so opredeljeni v Uredbi (ES) št. 1272/2008

Toksikološki podatki izdelka:

a) akutna strupenost	Ni klasificirano
	Na podlagi razpoložljivih podatkov merila za razvrstitev niso izpolnjena.
b) jedkost za kožo/draženje kože	Ni klasificirano
	Na podlagi razpoložljivih podatkov merila za razvrstitev niso izpolnjena.
c) resne okvare oči/draženje	Proizvod je razvrščen: Eye Irrit. 2(H319)
d) preobčutljivost pri vdihavanju in preobčutljivost kože	Ni klasificirano
	Na podlagi razpoložljivih podatkov merila za razvrstitev niso izpolnjena.
e) mutagenost za zarodne celice	Ni klasificirano
	Na podlagi razpoložljivih podatkov merila za razvrstitev niso izpolnjena.
f) rakotvornost	Ni klasificirano
	Na podlagi razpoložljivih podatkov merila za razvrstitev niso izpolnjena.
g) strupenost za razmnoževanje	Ni klasificirano
	Na podlagi razpoložljivih podatkov merila za razvrstitev niso izpolnjena.
h) STOT - enkratna izpostavljenost	Proizvod je razvrščen: STOT SE 3(H336)
i) STOT - ponavljajoča se izpostavljenost	Ni klasificirano
	Na podlagi razpoložljivih podatkov merila za razvrstitev niso izpolnjena.
j) nevarnost pri vdihavanju	Ni klasificirano
	Na podlagi razpoložljivih podatkov merila za razvrstitev niso izpolnjena.

Toksikološki podatki glavnih snovi, ki jih najdemo v izdelku:

etil acetat	a) akutna strupenost	LD50 Oralno Podgana 4934 mg/kg LD50 Koža Zajec > 20000 mg/kg LC50 Vdihavanje hlapov Podgana > 22.5 mg/l 6h
n-butil acetat	a) akutna strupenost	LD50 Oralno Podgana 10760 mg/kg LD50 Koža Zajec 14112 mg/kg LC50 Vdihavanje hlapov Podgana > 21.1 mg/l 4h

11.2 Podatki o drugih nevarnostih

Lastnosti endokrinih motilcev:

Ni endokrinih motilcev v koncentraciji > = 0,1%.

ODDELEK 12: Ekološki podatki

Uporabljajte v skladu z dobrimi delovnimi navadami, izogibajte se odlaganju izdelka v okolju.

12.1 Strupenost

Ekotoksikološki podatki:

Ekotoksikoloških lastnosti izdelka

Ni razvrščeno kot nevarno za okolje
Za izdelek ni razpoložljivih podatkov

Seznam sestavin z ekotoksikološkimi lastnostmi

Sestavina	Ident. št.	Ekotoksikološki podatki
etil acetat	CAS: 141-78-6 - EINECS: 205- 500-4 - INDEX: 607-022-00-5	a) akutna strupenost za vodno okolje : LC50 Riba 230 mg/l 96h
		a) akutna strupenost za vodno okolje : EC50 Vodna bolha 165 mg/l 48h
n-butil acetat	CAS: 123-86-4 - EINECS: 204- 658-1 - INDEX: 607-025-00-1	a) akutna strupenost za vodno okolje : LC50 Riba 18 mg/l 96h
		a) akutna strupenost za vodno okolje : EC50 Vodna bolha 44 mg/l 48h

a) akutna strupenost za vodno okolje : EC50 Alge 675 mg/l 72h

b) kronična strupenost za vodno okolje : NOEC Vodna bolha 23 mg/l - 21d

12.2 Obstočnost in razgradljivost

Sestavina	Obstočnost/razgradljivost:
etil acetat	Hitro razgradljivo
n-butil acetat	Hitro razgradljivo

12.3 Zmožnost kopičenja v organizmih

ni znano

12.4 Mobilnost v tleh

ni znano

12.5 Rezultati ocene PBT in vPvB

Na podlagi razpoložljivih podatkov, preparat ne vsebuje snovi PBT/vPvB v procentu $\geq 0.1\%$.

12.6 Lastnosti endokrinih motilcev

Ni endokrinih motilcev v koncentraciji $\geq 0,1\%$.

12.7 Drugi škodljivi učinki

ni znano

ODDELEK 13: Odstranjevanje

13.1 Metode ravnanja z odpadki

Če je mogoče, predelajte. Pošljite v usposobljena odlagališča ali v zažig pod kontroliranimi pogoji. Ravnajte se po lokalnih in državnih normah.

Ne dopustite, da pride v kanalizacijo ali vodne poti.

Odstraniti posode, ki jih kontaminira izdelka v skladu z lokalnimi ali nacionalnimi predpisi.

ODDELEK 14: Podatki o prevozu



14.1 Številka ZN in številka ID

1993

14.2 Pravilno odpremno ime ZN

ADR-uradno ime blaga: FLAMMABLE LIQUID, N.O.S. (etil acetat - n-butil acetat)

IATA-tehnično ime blaga: FLAMMABLE LIQUID, N.O.S. (etil acetat - n-butil acetat)

IMDG-tehnično ime blaga: FLAMMABLE LIQUID, N.O.S. (etil acetat - n-butil acetat)

14.3 Razredi nevarnosti prevoza

ADR-Razred: 3

IATA-razred: 3

IMDG-razred: 3

14.4 Skupina embalaže

ADR-embalažna skupina: II

IATA-embalažna skupina: II

IMDG-embalažna skupina: II

14.5 Nevarnosti za okolje

Onesnaževalec morja: Ne

Onesnažuje okolje po: Ne

IMDG-EMS: F-E, S-E

14.6 Posebni previdnostni ukrepi za uporabnika

Cestni in železniški transport (ADR-RID):

ADR-nalepka nevarnosti: 3

ADR - Identifikacijska številka nevarnosti: 33

ADR-posebni ukrepi: 274 601 640D

ADR-Pravilnik o cestnem prevozu nevarnega blaga:

Zračni transport (IATA):

IATA-potniška letala: 353

IATA-tovorna letala: 364

IATA-nalepka: 3

IATA-Stranske nevarnosti: -

IATA-Erg: 3H

IATA-posebni ukrepi: A3

Morski transport (IMDG):

IMDG-skladiščenje, kodeks: Category B

IMDG-skladiščenje, opomba: -

IMDG-Stranske nevarnosti: -

IMDG-posebni ukrepi: 274

14.7 Pomorski prevoz v razsutem stanju v skladu z instrumenti IMO

ni znano

ODDELEK 15: Zakonsko predpisani podatki

15.1 Predpisi/zakonodaja o zdravju, varnosti in okolju, specifični za snov ali zmes

Dir. 98/24/ES (Varovanje delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu)

Dir. 2000/39/ES (mejne vrednosti za poklicno izpostavljenost)

Direktiva 2010/75/EU

Uredba (ES) št. 1907/2006 (REACH)

Uredba (ES) št. 1272/2008 (CLP)

Uredba (ES) št. 790/2009 (1. ATP CLP) in (EU) št. 758/2013

Uredba (EU) 2020/878

Uredba (EU) št. 286/2011 (2. ATP CLP)

Uredba (EU) št. 618/2012 (3. ATP CLP)

Uredba (EU) št. 487/2013 (4. ATP CLP)

Uredba (EU) št. 944/2013 (5. ATP CLP)

Uredba (EU) št. 605/2014 (6. ATP CLP)

Uredba (EU) 2015/1221 (7. ATP CLP)

Uredba (EU) 2016/918 (8. ATP CLP)

Uredba (EU) 2016/1179 (9. ATP CLP)

Uredba (EU) 2017/776 (10. ATP CLP)

Uredba (EU) 2018/669 (11. ATP CLP)

Uredba (EU) 2018/1480 (13. ATP CLP)

Uredba (EU) 2019/521 (12. ATP CLP)

Uredba (EU) 2020/217 (14. ATP CLP)

Uredba (EU) 2020/1182 (15. ATP CLP)

Uredba (EU) 2021/643 (16. ATP CLP)

Uredba (EU) 2021/849 (17. ATP CLP)

Uredba (EU) 2022/692 (18. ATP CLP)

Omejitve, povezane z izdelkom ali vsebovanimi snovmi, v skladu s Prilogo XVII Uredbe (ES) 1907/2006 (REACH) in poznejše spremembe:

Obmedzenia vo vzťahu s výrobkom: 3, 40

Obmedzenia vo vzťahu s obsiahnutými látkami: 75

Določbe v zvezi z direktivo EU 2012/18 (Seveso III)

Kategorija Seveso III v skladu s Prilogo 1, del 1	Mejna vrednost nižje stopnje (v tonah)	Mejna vrednost višje stopnje (v tonah)
izdelek spada v kategorijo: P5c	5000	50000

Uredba (EU) št. 649/2012 (uredba PIC)

Snovi niso navedene

Nemški razred nevarnosti za vodo.

1: Low hazard to waters

SVHC snovi:

Na podlagi razpoložljivih podatkov, preparat ne vsebuje snovi SVHC v procentu $\geq 0.1\%$.

15.2 Ocena kemijske varnosti

Ocena kemijske varnosti ni bila opravljena za mešanice

ODDELEK 16: Drugi podatki

Številka	Opis
EUH066	Ponavljajoča izpostavljenost lahko povzroči nastanek suhe ali razpokane kože.
H225	Lahko vnetljiva tekočina in hlapi.
H226	Vnetljiva tekočina in hlapi.
H319	Povzroča hudo draženje oči.
H336	Lahko povzroči zaspanost ali omotico.

Številka	Razred in kategorija nevarnosti	Opis
2.6/2	Flam. Liq. 2	Vnetljiva tekočina, Kategorija 2
2.6/3	Flam. Liq. 3	Vnetljiva tekočina, Kategorija 3
3.3/2	Eye Irrit. 2	Draženje oči, Kategorija 2
3.8/3	STOT SE 3	Specifična strupenost za ciljne organe (STOT) – enkratna izpostavljenost STOT enkrat, Kategorija 3

Razvrstitev in postopek, uporabljen za izpeljavo razvrstitve za zmesi v skladu z Uredbo (ES) 1272/2008 [uredba CLP]:

Razvrstitev v skladu z Uredbo (ES) št. 1272/2008 Postopek razvrščanja

2.6/2	na podlagi podatkov o preskusih
3.3/2	metoda izračuna
3.8/3	metoda izračuna

Ta dokument je pripravila pristojna oseba, ki je ustrezno usposobljena

Glavni bibliografski viri:

ECDIN – Informacijska mreža za okoljske podatke za kemikalije – Skupno raziskovalno središče, Komisija Evropskih skupnosti
SAX – NEVARNE LASTNOSTI INDUSTRIJSKIH MATERIALOV – 8. izdaja – Van Nostrand Reinold
Varnostni listi dobaviteljev surovin.
CCNL - All. 1

Predstavljene informacije se nanašajo na naše znanje v zgoraj navedenem datumu. Nanašajo se zgolj na omenjeni izdelek in ne predstavljajo garancije za posebno kakovost.

Uporabnik je dolžan preveriti pravilnost in popolnost teh informacij glede na svojo specifično uporabo.

Ta list razveljavlja in nadomešča vsako predhodno izdajo

Legenda okrajšav in kratic, uporabljenih v varnostnem listu:

ACGIH: Ameriška konferenca vladnih industrijskih higienikov
ADR: Evropski sporazum o mednarodnem prevozu nevarnih snovi v cestnem prometu.
ATE: Ocena akutne strupenosti
ATEmix: Ocena akutne strupenosti (Zmesi)
BEI: Biološki indeks izpostavljenosti
CAS: Chemical Abstracts Service (oddelek Ameriškega kemijskega društva).
CAV: Center za zastupitve
CE: Evropska skupnost
CLP: Razvrščanje, etiketiranje, pakiranje.
CMR: Rakotvorno, mutageno in strupeno za razmnoževanje
COV: Hlapna organska spojina
CSA: Ocena kemijske varnosti
CSR: Poročilo o kemijski varnosti
DNEL: Izpeljane vrednosti brez učinka.
EC50: Srednja učinkovita koncentracija
ECHA: Evropska agencija za kemikalije
EINECS: Evropski seznam obstoječih snovi.
ES: Scenarij izpostavljenosti
GefStoffVO: Odlok o nevarnih snoveh, Nemčija.
GHS: Globalno poenoten sistem razvrščanja in označevanja nevarnih kemikalij.
IARC: Mednarodna agencija za raziskovanje raka
IATA: Mednarodno združenje za zračni transport.
IC50: Srednja inhibitorna koncentracija
IMDG: Mednarodni kodeks za prevoz nevarnega blaga po morju
LC50: Letalna koncentracija za 50 odstotkov testne populacije.
LD50: Letalna doza za 50 odstotkov testne populacije.
LDLo: Najnižja smrtna doza
N.A.: Se ne uporablja

N/A: Se ne uporablja
N/D: Ni opredeljeno/Ni razpoložljiv
N.D.: Ni razpoložljiv
NIOSH: Nacionalni inštitut za varnost in zdravje pri delu
NOAEL: Raven brez opaznih negativnih vplivov
OSHA: Upravljanje varnosti in zdravja pri delu
PBT: Obstoje, se kopičijo v organizmih in so strupene
PGK: Navodila za embalažo nevarnih snovi
PNEC: Predvidena koncentracija brez učinka.
PSG: Potniki
RID: Pravilnik o mednarodnem prevozu nevarnega blaga po železnici.
STEL: Meja za kratkotrajno izpostavljenost.
STOT: Specifično strupeno za ciljne organe.
TLV: Mejna vrednost izpostavljenosti.
TLV-TWA: Mejna vrednost izpostavljenosti v časovnem obdobju po 8 ur dnevno (ACGIH standard).
vPvB: Telo obstojno, se zelo lahko kopiči v organizmih.
WGK: Nemški razred nevarnosti za vodo.

Ethyl acetate

Substance identification

Chemical Name: Ethyl acetate

CAS number: 141-78-6

ETHYL ACETATE

ES 1: Cosmetics, personal care products (PC39); User for consumers (SU21).

ES 2: Filling of drums and small packages (CS6); INDUSTRIAL USES (SU3).

ES 3: Formulation or repackaging (F); INDUSTRIAL USES (SU3).

ES 4: Use of non-reactive processing aid at industrial site (no inclusion in article) (ERC4); Industrial uses (su3); Extraction agents (PC40).

ES 5: PROFESSIONAL APPLICATION OF COATINGS AND INKS; INDUSTRIAL USES (SU3).

ES 6: Use as laboratory reagent (PROC15); Industrial uses (su3); Industrial use.

ES 7: Use in cleaning products (GEST4_I, GEST4_P, GEST4_C); INDUSTRIAL USES (SU3).

ES 8: Use in lubricants (GEST6_I, GEST6_P, GEST6_C); INDUSTRIAL USES (SU3).

ES 9: Professional application of coatings and inks (14); INDUSTRIAL USES (SU3). Covers use in coatings (paints, inks, adhesives, etc.) including exposures during use (receipt of material, storage, preparation and transfer of bulk and semi-bulk products, application by spray, roller or spreader, dipping, flow, fluidized bed on production lines and film formation), the cleaning and maintenance of the equipment and the associated laboratory activities [GES3_I].

ES 10: Use as laboratory reagent (PROC15); Industrial uses (su3); Professional (G27).

ES 11: Use in agrochemical products (GEST11_P, GEST11_C); INDUSTRIAL USES (SU3).

ES 12: Use in detergent products (GEST4_I, GEST4_P, GEST4_C).

ES 13: Use in lubricants (GEST6_I, GEST6_P, GEST6_C)

ES 14: Adhesives, Sealants (PC1); Use in coatings (GEST3_I, GEST3_P, GEST3_C).

ES 5: PROFESSIONAL APPLICATION OF COATINGS AND INKS (17); INDUSTRIAL USES (SU3).

5.1. USE AT INDUSTRIAL SITES

Environment

SC 1: Use of non-reactive processing aid at industrial site (no inclusion in article) ERC4

Worker

SC 2: Generalized exposures (closed systems) PROC1

SC 3: Generalized exposures (closed systems); Use in closed systems, with sample taking PROC2

SC 4: Film formation - forced drying (50 -100°C). Stove (>100°C), Curing by UV/EB radiation PROC2

SC 5: Mixing operations, Generalized exposures PROC3

SC 6: Film formation, air drying PROC4

SC 7: Preparation of material for application, Mixing operations (open systems) PROC5

SC 8: Spraying (automatic/robotic) PROC7

SC 9: Manual spraying PROC7

SC 10: Material transfers, Non-Specialized site PROC8a

SC 11: Material transfers, Specialized site PROC8b

SC 12: Roller, diffusion, flow application PROC10

SC 13: Immersion, dipping and pouring PROC13

SC 14: Laboratory activities PROC15

SC 15: Material transfers, Drum/batch transfers, Transfer from/pour from containers PROC9

SC 16: Production or preparation of articles by tableting, compression, extrusion or pelettisation. PROC14

5.2. CONDITIONS OF USE THAT AFFECT EXPOSURE

5.2.1 Environmental exposure control: Use of non-reactive processing aid at industrial site (no inclusion in article) (ERC4)

Amount used (or contained in articles), frequency and duration of use/exposure

Daily amount per site: ≤ 1 t/day

Annual amount per site: ≤ 300 t/year

Organizational and technical measures and conditions

A wastewater treatment plant is expected.

Assumed domestic sewage treatment plant flow: ≥ 2E³ m³/day.

Conditions and measures for waste treatment (including the article of waste)

Waste treatment: Dispose of waste products or used containers according to local regulations.

Other conditions affecting environmental exposure

Water flow on the receiving surface: 18,000 m³/day.

5.2.2. Worker Exposure Control: Chemical production or refinement in closed processes without likelihood of exposure or in processes with equivalent containment conditions (PROC1)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.3. Worker Exposure Control: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.4. Worker Exposure Control: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.5. Worker Exposure Control: Chemical production or formulation in closed batch processes, with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.6. Worker Exposure Control: Production of chemicals with the possibility of exposure (PROC4)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.7. Worker Exposure Control: Mixing or blending in batch processes (PROC5)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.8. Worker Exposure Control: Industrial spraying (PROC7)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 95%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.9. Worker Exposure Control: Industrial spraying (PROC7)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 95%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.10. Worker Exposure Control: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.11. Worker Exposure Control: Transfer of a substance or a mixture (charging/discharging) at dedicated facilities (PROC8b)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 95%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.12. Worker Exposure Control: Application with rollers or brushes (PROC10)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.13. Worker Exposure Control: Treatment of articles by dipping and pouring (PROC13)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.14. Worker Exposure Control: Use as laboratory reagents (PROC15)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.15. Worker Exposure Control: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.16. Worker Exposure Control: Tableting, compression, extrusion, pelletising, granulation (PROC14)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

5.3.1. Environmental release and exposure: Use of non-reactive processing aid at industrial site (no inclusion in article) (ERC4)

Route release	Release rate	Method for estimating for release
water	20 kg/day	Estimated release factor
air	980 kg/day	Estimated release factor
Soil	0 kg/day	Estimated release factor

Protection target	Estimated exposure	RCR
Fresh water	0.119 mg/l (EUSES v2.1)	0,495
freshwater sediments	0.708 mg/kg dry weight (EUSES v2.1)	0,616
Sea water	0.012 mg/l (EUSES v2.1)	0,495
Marine sediment	0.071 mg/kg dry weight (EUSES v2.1)	0,617
Sewage treatment plant	1.184 mg/l (EUSES v2.1)	< 0.01
Farmland	0.081 mg/kg dry weight (EUSES v2.1)	0,547
Prey for predators (freshwater)	1.469 mg/kg dry weight (EUSES v2.1)	< 0.01
Prey for predators (marine water)	0.148 mg/kg dry weight (EUSES v2.1)	< 0.01
Main predator prey (marine water)	0.031 mg/kg dry weight (EUSES v2.1)	< 0.01
Prey for Predators (Terrestrial)	0.028 mg/kg dry weight (EUSES v2.1)	< 0.01

5.3.2. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	0.037 mg/m ³ (ECETOC TRA worker v3)	< 0.01
inhalation	systemic	Short term	0.147 mg/m ³ (ECETOC TRA worker v3)	< 0.01
inhalation	local	Long-term	0.037 mg/m ³ (ECETOC TRA worker v3)	< 0.01
inhalation	local	Short term	0.147 mg/m ³ (ECETOC TRA worker v3)	< 0.01
dermal	systemic	Long-term	0.034 mg/kg p.c./day (ECETOC TRA worker v3)	< 0.01
combined routes	systemic	Long-term	/	< 0.01

5.3.3. Worker exposure: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	361.7 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	361.7 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	1.37 mg/kg p.c./day (ECETOC TRA worker v3)	0.022
combined routes	systemic	Long-term	/	0.147

5.3.4. Worker exposure: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	361.7 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	361.7 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	1.37 mg/kg p.c./day (ECETOC TRA worker v3)	0.022
combined routes	systemic	Long-term	/	0.147

5.3.5. Worker exposure: Chemical production or formulation in closed batch processes, with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	systemic	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
inhalation	local	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
dermal	systemic	Long-term	0.69 mg/kg p.c./day (ECETOC TRA worker v3)	0.011
combined routes	systemic	Long-term	/	0.261

5.3.6. Worker exposure: Production of chemicals with the possibility of exposure (PROC4)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	36.71 mg/m ³ (ECETOC TRA worker v3)	0.05
inhalation	systemic	Short term	146.8 mg/m ³ (ECETOC TRA worker v3)	0.1
inhalation	local	Long-term	36.71 mg/m ³ (ECETOC TRA worker v3)	0.05
inhalation	local	Short term	146.8 mg/m ³ (ECETOC TRA worker v3)	0.1
dermal	systemic	Long-term	6.86 mg/kg p.c./day (ECETOC TRA worker v3)	0.109
combined routes	systemic	Long-term	/	0.159

5.3.7. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	13.71 mg/kg p.c./day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.343

5.3.8. Worker exposure: Industrial spraying (PROC7)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	42.86 mg/kg p.c./day (ECETOC TRA worker v3)	0.68
combined routes	systemic	Long-term	/	0.805

5.3.9. Worker exposure: Industrial spraying (PROC7)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	42.86 mg/kg p.c./day (ECETOC TRA worker v3)	0.68
combined routes	systemic	Long-term	/	0.805

5.3.10. Worker exposure: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	13.71 mg/kg p.c./day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.343

5.3.11. Worker exposure: Transfer of a substance or a mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	27.53 mg/m ³ (ECETOC TRA worker v3)	0,038
inhalation	systemic	Short term	110.1 mg/m ³ (ECETOC TRA worker v3)	0,075
inhalation	local	Long-term	27.53 mg/m ³ (ECETOC TRA worker v3)	0,038
inhalation	local	Short term	110.1 mg/m ³ (ECETOC TRA worker v3)	0,075
dermal	systemic	Long-term	13.71 mg/kg p.c./day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.255

5.3.12. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	27.43 mg/kg p.c./day (ECETOC TRA worker v3)	0.435
combined routes	systemic	Long-term	/	0.56

5.3.13. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	13.71 mg/kg p.c./day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.343

5.3.14. Worker exposure: Use as laboratory reagents (PROC15)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	systemic	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
inhalation	local	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
dermal	systemic	Long-term	0.34 mg/kg p.c./day (ECETOC TRA worker v3)	< 0.01
combined routes	systemic	Long-term	/	0.255

5.3.15. Worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	73.42 mg/m ³ (ECETOC TRA worker v3)	0.1
inhalation	systemic	Short term	293.6 mg/m ³ (ECETOC TRA worker v3)	0.2
inhalation	local	Long-term	73.42 mg/m ³ (ECETOC TRA worker v3)	0.1
inhalation	local	Short term	293.6 mg/m ³ (ECETOC TRA worker v3)	0.2
dermal	systemic	Long-term	6.86 mg/kg p.c./day (ECETOC TRA worker v3)	0.109
combined routes	systemic	Long-term	/	0.209

5.3.16. Worker exposure: Tableting, compression, extrusion, pelletising, granulation (PROC14)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	3.43 mg/kg p.c./day (ECETOC TRA worker v3)	0.054
combined routes	systemic	Long-term	/	0.179

5.4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Guidance to check compliance with the exposure scenario: <https://echa.europa.eu/>

ES 9: PROFESSIONAL APPLICATION OF COATINGS AND INKS (14); INDUSTRIAL USES (SU3). COVERS USE IN COATINGS (PAINTS, INKS, ADHESIVES, ETC.) INCLUDING EXPOSURES DURING USE (RECEIPT OF MATERIAL, STORAGE, PREPARATION AND TRANSFER OF BULK AND SEMI-BULK PRODUCTS, APPLICATION BY SPRAY, ROLLER OR SPREADER, DIPPING, FLOW, FLUIDIZED BED ON PRODUCTION LINES AND FILM FORMATION), THE CLEANING AND MAINTENANCE OF THE EQUIPMENT AND THE ASSOCIATED LABORATORY ACTIVITIES [GES3_I].

9.1. WIDE DISPERSIVE USE BY PROFESSIONAL WORKERS

Environment

SC 1: Wide dispersive use of non-reactive processing aid (no inclusion into the article, outdoor) ERC8d

Worker

SC 3: Generalized exposures (closed systems) PROC1
SC 4: Filling of equipment from drums and containers PROC2
SC 5: Generalized exposures (closed systems), Use in closed systems PROC2
SC 6: Preparation of material for application, Generalized exposures PROC3
SC 7: Film formation - air drying, Indoor use PROC4
SC 8: Film formation - air drying, Outdoor use PROC4
SC 9: Preparation of material for application, Indoor use PROC5
SC 10: Preparation of material for application, Outdoor use PROC5
SC 11: Material transfers, Drum/batch transfers, Non-Specialized site PROC8a
SC 12: 12 Material Transfers, Drum/batch transfers, specialized site PROC8b
SC 13: Roller, diffusion, flow application, Indoor use PROC10
SC 14: Roller, diffusion, flow application, Outdoor use PROC10
SC 15: Manual spraying, Indoor use PROC11
SC 16: Manual spraying, Outdoor use PROC11
SC 17: Immersion, dipping and pouring, Indoor use PROC13
SC 18: Immersion, dipping and pouring, Outdoor use PROC13
SC 19: Laboratory activities PROC15
SC 20: Hand application - finger paints, crayons, stickers, Indoor use PROC19
SC 21: Hand application - finger paints, crayons, stickers, Outdoor use PROC19

9.2. CONDITIONS OF USE THAT AFFECT EXPOSURE

9.2.1 Environmental exposure control: Wide dispersive use of non-reactive processing aid (no inclusion into the article, outdoor) (ERC8d)

Organizational and technical measures and conditions

A wastewater treatment plant is expected.

Conditions and measures for waste treatment (including the article of waste)

Waste treatment: Dispose of waste products or used containers according to local regulations.

9.2.3. Worker Exposure Control: Chemical production or refinement in closed processes without likelihood of exposure or in processes with equivalent containment conditions (PROC1)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.4. Worker Exposure Control: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.5. Worker Exposure Control: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.6. Worker Exposure Control: Chemical production or formulation in closed batch processes, with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (3 to 5 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.7. Worker Exposure Control: Production of chemicals with the possibility of exposure (PROC4)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 80%

Provide a basic level of general ventilation (3 to 5 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.8. Worker Exposure Control: Production of chemicals with the possibility of exposure (PROC4)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Assumes that activities are undertaken with appropriate and well maintained equipment by trained personnel operating under supervision.

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.9. Worker Exposure Control: Mixing or blending in batch processes (PROC5)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 80%

Provide a basic level of general ventilation (3 to 5 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.10. Worker Exposure Control: Mixing or blending in batch processes (PROC5)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable respirator.

For more information, refer to Section 8 of the SDS (safety data sheet).

Inhalation - minimum yield of 90%

Other conditions affecting worker exposure

Indoor and outdoor use: Outdoor use

Temperature: Process temperature up to 40°C is assumed

9.2.11. Worker Exposure Control: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a) (PROC8b)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (3 to 5 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.12. Worker Exposure Control: Transfer of a substance or a mixture (charging/discharging) at dedicated facilities (PROC8b)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 90%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.13. Worker Exposure Control: Application with rollers or brushes (PROC10)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 80%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.14. Worker Exposure Control: Application with rollers or brushes (PROC10)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable respirator.

For more information, refer to Section 8 of the SDS (safety data sheet).

Inhalation - minimum yield of 90%

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.15. Worker Exposure Control: Non-industrial spray application (PROC11)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 80%

Provide a basic level of general ventilation (3 to 5 air changes per hour).

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable gloves tested to EN374.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

For more information, refer to Section 8 of the SDS (safety data sheet).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.16. Worker Exposure Control: Non-industrial spray application (PROC11)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable gloves tested to EN374.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

For more information, refer to Section 8 of the SDS (safety data sheet).

Wear suitable respirator.

For more information, refer to Section 8 of the SDS (safety data sheet).

Inhalation - minimum yield of 90%

Other conditions affecting worker exposure

Indoor and outdoor use: Outdoor use

Temperature: Process temperature up to 40°C is assumed

9.2.17. Worker Exposure Control: Treatment of articles by dipping and pouring (PROC13)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.18. Worker Exposure Control: Treatment of articles by dipping and pouring (PROC13)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable respirator.

For more information, refer to Section 8 of the SDS (safety data sheet).

Inhalation - minimum yield of 90%

Other conditions affecting worker exposure

Indoor and outdoor use: Outdoor use

Temperature: Process temperature up to 40°C is assumed

9.2.19. Worker Exposure Control: Use as laboratory reagents (PROC15)

Product features (article)

Covers concentrations up to 100%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.20. Worker Exposure Control: Hand-mixing with direct contact and only PPE available (PROC19)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable gloves tested to EN374.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

For more information, refer to Section 8 of the SDS (safety data sheet).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.2.21. Worker Exposure Control: Hand-mixing with direct contact and only PPE available (PROC19)

Product features (article)

Covers concentrations up to 5 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable gloves tested to EN374.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

For more information, refer to Section 8 of the SDS (safety data sheet).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

9.3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

9.3.1. Environmental release and exposure: Wide dispersive use of non-reactive processing aid (no inclusion into the article, outdoor) (ERC8d)

Route release	Release rate	Method for estimating for release
water	0.014 kg/day	Estimated release factor
air	980 kg/day	Estimated release factor
Soil	0 kg/day	Estimated release factor

Protection target	Estimated exposure	RCR
Fresh water	0.000396 mg/l (EUSES v2.1)	< 0.01
freshwater sediments	0.00236 mg/kg dry weight (EUSES v2.1)	< 0.01
Sea water	0.0000597 mg/l (EUSES v2.1)	< 0.01
Marine sediment	0.000356 mg/kg dry weight (EUSES v2.1)	< 0.01
Sewage treatment plant	0.000805 mg/l (EUSES v2.1)	< 0.01
Farmland	0.000131 mg/kg dry weight (EUSES v2.1)	< 0.01
Prey for predators (freshwater)	0.011 mg/kg wet weight (EUSES v2.1)	< 0.01
Prey for predators (marine water)	0.00167 mg/kg wet weight (EUSES v2.1)	< 0.01
Main predator prey (marine water)	0.00158 mg/kg wet weight (EUSES v2.1)	< 0.01
Prey for Predators (Terrestrial)	0.000114 mg/kg wet weight (EUSES v2.1)	< 0.01

9.3.3. Worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	0.367 mg/m ³ (ECETOC TRA worker v3)	< 0.01
inhalation	systemic	Short term	1.468 mg/m ³ (ECETOC TRA worker v3)	< 0.01
inhalation	local	Long-term	0.367 mg/m ³ (ECETOC TRA worker v3)	< 0.01
inhalation	local	Short term	1.468 mg/m ³ (ECETOC TRA worker v3)	< 0.01
dermal	systemic	Long-term	0.034 mg/kg p.c./day (ECETOC TRA worker v3)	< 0.01
combined routes	systemic	Long-term	/	< 0.01

9.3.4. Worker exposure: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	systemic	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
inhalation	local	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
dermal	systemic	Long-term	1.37 mg/kg p.c./day (ECETOC TRA worker v3)	0.022
combined routes	systemic	Long-term	/	0.272

9.3.5. Worker exposure: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
inhalation	local	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	systemic	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
dermal	systemic	Long-term	1.37 mg/kg p.c./day (ECETOC TRA worker v3)	0.022
combined routes	systemic	Long-term	/	0.272

9.3.6. Worker exposure: Chemical production or formulation in closed batch processes, with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	0.69 mg/kg p.c./day (ECETOC TRA worker v3)	0.011
combined routes	systemic	Long-term	/	0.361

9.3.7. Worker exposure: Production of chemicals with the possibility of exposure (PROC4)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	128.4 mg/m ³ (ECETOC TRA worker v3)	0.175
inhalation	systemic	Short term	513.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Long-term	128.4 mg/m ³ (ECETOC TRA worker v3)	0.175
inhalation	local	Short term	513.9 mg/m ³ (ECETOC TRA worker v3)	0.35
dermal	systemic	Long-term	6.86 mg/kg p.c./day (ECETOC TRA worker v3)	0.109
combined routes	systemic	Long-term	/	0.284

9.3.8. Worker exposure: Production of chemicals with the possibility of exposure (PROC4)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	6.86 mg/kg p.c./day (ECETOC TRA worker v3)	0.109
combined routes	systemic	Long-term	/	0.459

9.3.9. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	13.71 mg/kg p.c./day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.568

9.3.10. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	128.4 mg/m ³ (ECETOC TRA worker v3)	0.175
inhalation	systemic	Short term	513.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Long-term	128.4 mg/m ³ (ECETOC TRA worker v3)	0.175
inhalation	local	Short term	513.9 mg/m ³ (ECETOC TRA worker v3)	0.35
dermal	systemic	Long-term	13.71 mg/kg p.c./day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.393

9.3.11. Worker exposure: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	13.71 mg/kg p.c./day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.568

9.3.12. Worker exposure: Transfer of a substance or a mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	systemic	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Long-term	91.77 mg/m ³ (ECETOC TRA worker v3)	0.125
inhalation	local	Short term	367.1 mg/m ³ (ECETOC TRA worker v3)	0.25
dermal	systemic	Long-term	13.71 mg/kg p.c./day (ECETOC TRA worker v3)	0.218
combined routes	systemic	Long-term	/	0.343

9.3.13. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	27.43 mg/kg p.c./day (ECETOC TRA worker v3)	0.435
combined routes	systemic	Long-term	/	0.785

9.3.14. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	128.4 mg/m ³ (ECETOC TRA worker v3)	0.175
inhalation	systemic	Short term	513.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Long-term	128.4 mg/m ³ (ECETOC TRA worker v3)	0.175
inhalation	local	Short term	513.9 mg/m ³ (ECETOC TRA worker v3)	0.35
dermal	systemic	Long-term	27.43 mg/kg p.c./day (ECETOC TRA worker v3)	0.435
combined routes	systemic	Long-term	/	0.61

9.3.15. Worker exposure: Non-industrial spray application (PROC11)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	308.3 mg/m ³ (ECETOC TRA worker v3)	0.42
inhalation	systemic	Short term	mg/m ³ (ECETOC TRA worker v3)	0.84
inhalation	local	Long-term	308.3 mg/m ³ (ECETOC TRA worker v3)	0.42
inhalation	local	Short term	mg/m ³ (ECETOC TRA worker v3)	0.84
dermal	systemic	Long-term	12.85 mg/kg p.c./day (ECETOC TRA worker v3)	0.204
combined routes	systemic	Long-term	/	0.624

9.3.16. Worker exposure: Non-industrial spray application (PROC11)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	154.1 mg/m ³ (ECETOC TRA worker v3)	0.21
inhalation	systemic	Short term	616.7 mg/m ³ (ECETOC TRA worker v3)	0.42
inhalation	local	Long-term	154.1 mg/m ³ (ECETOC TRA worker v3)	0.21
inhalation	local	Short term	616.7 mg/m ³ (ECETOC TRA worker v3)	0.42
dermal	systemic	Long-term	12.85 mg/kg p.c./day (ECETOC TRA worker v3)	0.204
combined routes	systemic	Long-term	/	0.414

9.3.17. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	systemic	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	local	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	local	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
dermal	systemic	Long-term	8.226 mg/kg p.c./day (ECETOC TRA worker v3)	0.131
combined routes	systemic	Long-term	/	0.356

9.3.18. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	38.54 mg/m ³ (ECETOC TRA worker v3)	0.053
inhalation	systemic	Short term	154.1 mg/m ³ (ECETOC TRA worker v3)	0.105
inhalation	local	Long-term	38.54 mg/m ³ (ECETOC TRA worker v3)	0.053
inhalation	local	Short term	154.1 mg/m ³ (ECETOC TRA worker v3)	0.105
dermal	systemic	Long-term	8.226 mg/kg p.c./day (ECETOC TRA worker v3)	0.131
combined routes	systemic	Long-term	/	0.183

9.3.19. Worker exposure: Use as laboratory reagents (PROC15)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	systemic	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
inhalation	local	Long-term	183.5 mg/m ³ (ECETOC TRA worker v3)	0.25
inhalation	local	Short term	734.2 mg/m ³ (ECETOC TRA worker v3)	0.5
dermal	systemic	Long-term	0.34 mg/kg p.c./day (ECETOC TRA worker v3)	< 0.01
combined routes	systemic	Long-term	/	0.255

9.3.20. Worker exposure: Hand-mixing with direct contact and only PPE available (PROC19)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	330.3 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	systemic	Short term	1.32 g/m ³ (ECETOC TRA worker v3)	0.9
inhalation	local	Long-term	330.3 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	local	Short term	1.32 g/m ³ (ECETOC TRA worker v3)	0.9
dermal	systemic	Long-term	16.97 mg/kg p.c./day (ECETOC TRA worker v3)	0.269
combined routes	systemic	Long-term	/	0.72

9.3.21. Worker exposure: Hand-mixing with direct contact and only PPE available (PROC19)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	mg/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	mg/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	5.657 mg/kg p.c./day (ECETOC TRA worker v3)	0.09
combined routes	systemic	Long-term	/	0.44

9.4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Guidance to check compliance with the exposure scenario: <https://echa.europa.eu/>

ES 12: USE IN DETERGENT PRODUCTS (GEST4_I, GEST4_P, GEST4_C).

12.1. WIDE DISPERSIVE USE BY PROFESSIONAL WORKERS

Environment

SC 1: Wide dispersive use of non-reactive processing aid (no inclusion into the article, indoors) ERC8a

Worker

SC 2: Filling of equipment from drums and containers, specialised site PROC8b

SC 3: Automated process with (semi) closed systems; Use in closed systems PROC2

SC 4: Automated process with (semi) closed systems Drum/batch transfers, Use in closed systems PROC3

SC 5: Semi-automatic process (e.g: Semi-automatic application of floor care and maintenance products) PROC4

SC 6: Filling of equipment from drums and containers, Outdoor use PROC8a

SC 7: Immersion, dipping and pouring, Manual, Surfaces, Cleaning PROC13

SC 8: Cleaning with low-pressure washers, Roller application or brushing, No spraying PROC10

SC 9: Cleaning with high pressure washers, Spraying, Indoor use PROC11

SC 10: Cleaning with high pressure washers Spraying, Outdoor use PROC11

SC 11: Application of cleaning products in closed systems, Manual, Surfaces, Cleaning PROC10

SC 12: Ad hoc manual application via trigger sprays, partial dipping, etc., Roller application or brushing PROC10

SC 13: Application of cleaning products in closed systems, Outdoor use PROC4

SC 14: Cleaning of medical devices PROC4

12.2. CONDITIONS OF USE THAT AFFECT EXPOSURE

12.2.1 Environmental exposure control: Wide dispersive use of non-reactive processing aid (no inclusion into the article, indoors) (ERC8a)

Organizational and technical measures and conditions

A wastewater treatment plant is expected.

Conditions and measures for waste treatment (including the article of waste)

Waste treatment: Dispose of waste products or used containers according to local regulations.

12.2.2. Worker Exposure Control: Transfer of a substance or a mixture (charging/discharging) at dedicated facilities (PROC8b)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.3. Worker Exposure Control: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.4. Worker Exposure Control: Chemical production or formulation in closed batch processes, with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.5. Worker Exposure Control: Production of chemicals with the possibility of exposure (PROC4)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.6. Worker Exposure Control: Transfer of a substance or a preparation (filling/emptying) at non-dedicated facilities (PROC8a)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable respirator.

For more information, refer to Section 8 of the SDS (safety data sheet).

Inhalation - minimum yield of 90%

Other conditions affecting worker exposure

Indoor and outdoor use: Outdoor use

Temperature: Process temperature up to 40°C is assumed

12.2.7. Worker Exposure Control: Treatment of articles by dipping and pouring (PROC13)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.8. Worker Exposure Control: Application with rollers or brushes (PROC10)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.9. Worker Exposure Control: Non-industrial spray application (PROC11)

Product features (article)

Covers concentrations up to 5 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (from 5 to 10 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.10. Worker Exposure Control: Non-industrial spray application (PROC11)

Product features (article)

Covers concentrations up to 1%.

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable gloves tested to EN374.

If skin contamination is expected to extend to other parts of the body, these parts should also be protected with impermeable clothing equivalent to that described for the hands.

For more information, refer to Section 8 of the SDS (safety data sheet).

Other conditions affecting worker exposure

Indoor and outdoor use: Outdoor use

Temperature: Process temperature up to 40°C is assumed

12.2.11. Worker Exposure Control: Application with rollers or brushes (PROC10)

Product features (article)

Covers concentrations up to 5 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

5.2.12. Worker Exposure Control: Application with rollers or brushes (PROC10)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 80%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.2.13. Worker Exposure Control: Production of chemicals with the possibility of exposure (PROC4)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Conditions and measures for personal protection, hygiene and health assessment

Wear suitable respirator.

For more information, refer to Section 8 of the SDS (safety data sheet).

Inhalation - minimum yield of 90%

Other conditions affecting worker exposure

Indoor and outdoor use: Outdoor use

Temperature: Process temperature up to 40°C is assumed

12.2.14. Worker Exposure Control: Production of chemicals with the possibility of exposure (PROC4)

Product features (article)

Covers concentrations up to 25 %

Amount used (or contained in articles), frequency and duration of use/exposure

Frequency of use: Covers use up to 8 h/day

Organizational and technical measures and conditions

Local exhaust ventilation

Inhalation - minimum yield of 80%

Provide a basic level of general ventilation (1 to 3 air changes per hour).

Other conditions affecting worker exposure

Indoor and outdoor use: Indoor use

Temperature: Process temperature up to 40°C is assumed

12.3. EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE

12.3.1. Environmental release and exposure: Wide dispersive use of non-reactive processing aid (no inclusion into the article, indoors) (ERC8a)

Route release	Release rate	Method for estimating for release
water	0.014 kg/day	Environmental Release Category (ERC)
air	0.014 kg/day	Environmental Release Category (ERC)
Soil	0 kg/day	Environmental Release Category (ERC)

Protection target	Estimated exposure	RCR
Fresh water	0.000397 mg/l (EUSES v2.1)	< 0.01
freshwater sediments	0.00237 mg/kg dry weight (EUSES v2.1)	< 0.01
Sea water	0.0000598 mg/l (EUSES v2.1)	< 0.01
Marine sediment	0.000357 mg/kg dry weight (EUSES v2.1)	< 0.01
Sewage treatment plant	0.000811 mg/l (EUSES v2.1)	< 0.01
Farmland	0.000131 mg/kg dry weight (EUSES v2.1)	< 0.01
Prey for predators (freshwater)	0.011 mg/kg dry weight (EUSES v2.1)	< 0.01
Prey for predators (marine water)	0.00167 mg/kg dry weight (EUSES v2.1)	< 0.01
Main predator prey (marine water)	0.00158 mg/kg dry weight (EUSES v2.1)	< 0.01
Prey for Predators (Terrestrial)	0.000114 mg/kg dry weight (EUSES v2.1)	< 0.01

12.3.2. Worker exposure: Transfer of a substance or a mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	systemic	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	local	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	local	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
dermal	systemic	Long-term	8.226 mg/kg p.c./day (ECETOC TRA worker v3)	0.131
combined routes	systemic	Long-term	/	0.356

12.3.3. Worker exposure: Chemical production or refinery in closed process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	110.1 mg/m ³ (ECETOC TRA worker v3)	0.15
inhalation	local	Long-term	110.1 mg/m ³ (ECETOC TRA worker v3)	0.15
inhalation	local	Short term	440.5 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	systemic	Short term	440.5 mg/m ³ (ECETOC TRA worker v3)	0.3
dermal	systemic	Long-term	0.822 mg/kg p.c./day (ECETOC TRA worker v3)	0.013
combined routes	systemic	Long-term	/	0.163

12.3.4. Worker exposure: Chemical production or formulation in closed batch processes, with occasional controlled exposure or processes with equivalent containment conditions (PROC3)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	220.2 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	systemic	Short term	881.0 mg/m ³ (ECETOC TRA worker v3)	0.6
inhalation	local	Long-term	220.2 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	local	Short term	881.0 mg/m ³ (ECETOC TRA worker v3)	0.6
dermal	systemic	Long-term	0.414 mg/kg p.c./day (ECETOC TRA worker v3)	< 0.01
combined routes	systemic	Long-term	/	0.307

12.3.5. Worker exposure: Production of chemicals with the possibility of exposure (PROC4)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	systemic	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	local	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	local	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
dermal	systemic	Long-term	4.116 mg/kg p.c./day (ECETOC TRA worker v3)	0.065
combined routes	systemic	Long-term	/	0.29

12.3.6. Worker exposure: Transfer of substance or preparation (charging/discharging) at non dedicated facilities (PROC8a)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	77.09 mg/m ³ (ECETOC TRA worker v3)	0.105
inhalation	systemic	Short term	308.3 mg/m ³ (ECETOC TRA worker v3)	0.21
inhalation	local	Long-term	77.09 mg/m ³ (ECETOC TRA worker v3)	0.105
inhalation	local	Short term	308.3 mg/m ³ (ECETOC TRA worker v3)	0.21
dermal	systemic	Long-term	8.226 mg/kg p.c./day (ECETOC TRA worker v3)	0.131
combined routes	systemic	Long-term	/	0.236

12.3.7. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	systemic	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	local	Long-term	165.1 mg/m ³ (ECETOC TRA worker v3)	0.225
inhalation	local	Short term	660.7 mg/m ³ (ECETOC TRA worker v3)	0.45
dermal	systemic	Long-term	8.226 mg/kg p.c./day (ECETOC TRA worker v3)	0.131
combined routes	systemic	Long-term	/	0.356

12.3.8. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	330.3 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	systemic	Short term	mg/m ³ (ECETOC TRA worker v3)	0.9
inhalation	local	Long-term	330.3 mg/m ³ (ECETOC TRA worker v3)	0.45
inhalation	local	Short term	mg/m ³ (ECETOC TRA worker v3)	0.9
dermal	systemic	Long-term	16.45 mg/kg p.c./day (ECETOC TRA worker v3)	0.261
combined routes	systemic	Long-term	/	0.711

12.3.9. Worker exposure: Non-industrial spray application (PROC11)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	220.2 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	systemic	Short term	881.0 mg/m ³ (ECETOC TRA worker v3)	0.6
inhalation	local	Long-term	220.2 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	local	Short term	881.0 mg/m ³ (ECETOC TRA worker v3)	0.6
dermal	systemic	Long-term	21.42 mg/kg p.c./day (ECETOC TRA worker v3)	0.34
combined routes	systemic	Long-term	/	0.64

12.3.10. Worker exposure: Non-industrial spray application (PROC11)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	2.143 mg/kg p.c./day (ECETOC TRA worker v3)	0.034
combined routes	systemic	Long-term	/	0.384

12.3.11. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	systemic	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
inhalation	local	Long-term	256.9 mg/m ³ (ECETOC TRA worker v3)	0.35
inhalation	local	Short term	1.03 g/m ³ (ECETOC TRA worker v3)	0.7
dermal	systemic	Long-term	5.486 mg/kg p.c./day (ECETOC TRA worker v3)	0.087
combined routes	systemic	Long-term	/	0.437

12.3.12. Worker exposure: Application with rollers or brushes (PROC10)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	220.2 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	systemic	Short term	881.0 mg/m ³ (ECETOC TRA worker v3)	0.6
inhalation	local	Long-term	220.2 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	local	Short term	881.0 mg/m ³ (ECETOC TRA worker v3)	0.6
dermal	systemic	Long-term	16.45 mg/kg p.c./day (ECETOC TRA worker v3)	0.261
combined routes	systemic	Long-term	/	0.561

12.3.13. Worker exposure: Production of chemicals with the possibility of exposure (PROC4)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	38.54 mg/m ³ (ECETOC TRA worker v3)	0.053
inhalation	systemic	Short term	154.1 mg/m ³ (ECETOC TRA worker v3)	0.105
inhalation	local	Long-term	38.54 mg/m ³ (ECETOC TRA worker v3)	0.053
inhalation	local	Short term	154.1 mg/m ³ (ECETOC TRA worker v3)	0.105
dermal	systemic	Long-term	4.116 mg/kg p.c./day (ECETOC TRA worker v3)	0.065
combined routes	systemic	Long-term	/	0.118

12.3.14. Worker exposure: Production of chemicals with the possibility of exposure (PROC4)

Exposure routes	Health effect	Exposure indicator	Estimated exposure	RCR
inhalation	systemic	Long-term	110.1 mg/m ³ (ECETOC TRA worker v3)	0.15
inhalation	systemic	Short term	440.5 mg/m ³ (ECETOC TRA worker v3)	0.3
inhalation	local	Long-term	110.1 mg/m ³ (ECETOC TRA worker v3)	0.15
inhalation	local	Short term	440.5 mg/m ³ (ECETOC TRA worker v3)	0.3
dermal	systemic	Long-term	4.116 mg/kg p.c./day (ECETOC TRA worker v3)	0.065
combined routes	systemic	Long-term	/	0.215

12.4. GUIDANCE FOR DOWNSTREAM USERS TO ASSESS WHETHER THEY COMPLY WITH THE LIMITS SET BY THE EXPOSURE SCENARIO

Guidance to check compliance with the exposure scenario: <https://echa.europa.eu/>

n-butyl acetate

Substance identification

Chemical Name: n-butyl acetate

CAS number: 123-86-4

Date - Version: 07/06/2017 10.0

1. USE IN COATINGS. USE IN PAINTS. USE IN PRINTING INKS. USE IN ADHESIVES.

Short title of the exposure scenario: Use in coatings. Use in paints. Use in printing inks. Use in adhesives.

SU3; ERC4; PROC7, PROC10, PROC13

EXPOSURE CONTROL AND RISK MANAGEMENT MEASURES

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: CEPE SPERC4.1a.v1

Operating conditions

Yearly amount used in EU: 5,000,000 kgs

Minimum emission days per year: 225

Emission factor to air: 0.8%

Emission factor in water: 2%

Emission factor in soil: 0%

Receiving surface water (flow rate): 18,000 m³/day

Freshwater dilution factor: 10

Marine water dilution factor: 100

Risk management measures

Suitable measures to reduce emissions to air can be: Exhaust gas treatment with thermal oxidation.

Type of treatment plant: Municipal sewage treatment plant.

Assumed sewage treatment plant flow: 2,000 m³/day

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Environment

Risk Characterization Ratio (RCR): 0.925355

Risk from environmental exposure is driven by soil.

Maximum safe use amount: 1080.7 kg/day

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC7: Industrial spray application

Area of use: Industrial

Operating conditions

Substance concentration: n-butyl acetate content: ≥0 - ≤100%

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 480 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%
Minimize manual tasks.
Daily general cleaning of equipment and work area.
Regular inspection and maintenance of equipment and machinery.
Ensure that the activity is performed outside the operator's respiratory zone (head-product distance greater than 1m).
Avoid frequent and direct contact with the substance.
Check that risk reduction measures are implemented and that the conditions of use are respected.
Avoid splashes.
Make sure the spray booth is used.
Wear suitable clothing.

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.
Exposure estimation: 4.2857 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.38961
Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.
Exposure estimation: 0.0001 mg/m³
Risk Characterization Ratio (RCR): 0.000001

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra> Please note that a revised version was used (see exposure estimates).

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC10: Application with rollers or brushes

Area of use: Industrial

Operating conditions

Substance concentration: n-butyl acetate content: ≥ 0 - $\leq 100\%$
Physical state: liquid
Vapor pressure of the substance during use: 1120Pa
Process temperature: 20°C
Duration and frequency of application: 480 mins. 5 days a week
Indoor/Outdoor: Internal use

Risk management measures

Forced local ventilation. Effectiveness: 90%
Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.
Exposure estimation: 2.7429 mg/kg/day (body weight)
Risk Characterization Ratio (RCR): 0.249351
Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.
Exposure estimation: 24.1996 mg/m³
Risk Characterization Ratio (RCR): 0.080665

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra>

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC13: Treatment of articles by dipping and pouring

Area of use: Industrial

Operating conditions

Substance concentration: n-butyl acetate content: ≥ 0 - $\leq 100\%$

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 480 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Forced local ventilation. Effectiveness: 90%

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.

Exposure estimation: 1.3714 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.124675

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.

Exposure estimation: 24.1996 mg/m³

Risk Characterization Ratio (RCR): 0.080665

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra>

2. USE IN COATINGS. USE IN PAINTS. USE IN PRINTING INKS. USE IN ADHESIVES.

Short title of the exposure scenario: Use in coatings. Use in paints. Use in printing inks. Use in adhesives.
SU3; ERC4; PROC7, PROC10, PROC13

EXPOSURE CONTROL AND RISK MANAGEMENT MEASURES

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: CEPE SPERC4.1a.v1

Operating conditions

Yearly amount used in EU: 43,000,000 kgs

Minimum emission days per year: 225

Emission factor to air: 0.8%

Emission factor in water: 2%

Emission factor in soil: 0%

Receiving surface water (flow rate): 18,000 m³/day

Freshwater dilution factor: 10

Marine water dilution factor: 100

Risk management measures

Suitable measures to reduce emissions to air can be: Exhaust gas treatment with thermal oxidation.

Type of treatment plant: Municipal sewage treatment plant.

Assumed sewage treatment plant flow: 2,000 m³/day

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Environment

Risk Characterization Ratio (RCR): 0.925355

Risk from environmental exposure is driven by soil.

Maximum safe use amount: 1080.7 kg/day

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC7: Industrial spray application

Area of use: Industrial

Operating conditions

Substance concentration: n-butyl acetate content: ≥0 - ≤100%

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 480 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Minimize manual tasks.

Daily general cleaning of equipment and work area.

Regular inspection and maintenance of equipment and machinery.

Ensure that the activity is performed outside the operator's respiratory zone (head-product distance greater than 1m).

Avoid frequent and direct contact with the substance.

Check that risk reduction measures are implemented and that the conditions of use are respected.

Avoid splashes.

Make sure the spray booth is used.

Wear suitable clothing.

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.

Exposure estimation: 4.2857 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.38961

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.
Exposure estimation: 0.0001 mg/m³
Risk Characterization Ratio (RCR): 0.000001

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra> Please note that a revised version was used (see exposure estimates).

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC10: Application with rollers or brushes

Area of use: Industrial

Operating conditions

Substance concentration: n-butyl acetate content: ≥0 - ≤100%

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 480 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Forced local ventilation. Effectiveness: 90%

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.

Exposure estimation: 2.7429 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.249351

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.

Exposure estimation: 24.1996 mg/m³

Risk Characterization Ratio (RCR): 0.080665

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra>

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC13: Treatment of articles by dipping and pouring

Area of use: Industrial

Operating conditions

Substance concentration: n-butyl acetate content: ≥0 - ≤100%

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 480 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Forced local ventilation. Effectiveness: 90%

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.

Exposure estimation: 1.3714 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.124675

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.

Exposure estimation: 24.1996 mg/m³

Risk Characterization Ratio (RCR): 0.080665

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra>

3. USE IN COATINGS. USE IN PAINTS. USE IN PRINTING INKS. USE IN ADHESIVES.

Short title of the exposure scenario: Use in coatings. Use in paints. Use in printing inks. Use in adhesives.
SU22; ERC8a, ERC8d; PROC10, PROC11, PROC13, PROC19

EXPOSURE CONTROL AND RISK MANAGEMENT MEASURES

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: CEPE SPERC 8a.2a.v1

Operating conditions

Yearly amount used in EU: 2,000,000 kgs

Minimum emission days per year: 225

Emission factor to air: 99%

Emission factor in water: 1%

Emission factor in soil: 0%

Receiving surface water (flow rate): 18,000 m³/day

Freshwater dilution factor: 10

Marine water dilution factor: 100

Risk management measures

The wastewater treatment measures considered suitable are, for example, wastewater or sewage treatment plant.

Type of treatment plant: Municipal sewage treatment plant.

Assumed sewage treatment plant flow: 2,000 m³/day

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Environment

Risk Characterization Ratio (RCR): 0.012923

Risk from environmental exposure is driven by freshwater sediment.

Maximum safe use amount: 1934.6 kg/giorno

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: CEPE SPERC 8d.3a.v1

Operating conditions

Yearly amount used in EU: 2,000,000 kgs

Minimum emission days per year: 225

Emission factor to air: 98%

Emission factor in water: 2%

Emission factor in soil: 0%

Receiving surface water (flow rate): 18,000 m³/day

Freshwater dilution factor: 10

Marine water dilution factor: 100

Risk management measures

Type of treatment plant: Municipal sewage treatment plant.

Assumed sewage treatment plant flow: 2,000 m³/day

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Environment

Risk Characterization Ratio (RCR): 0.092422

Risk from environmental exposure is driven by soil.

Maximum safe use amount: 1082 kg/day

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC10: Application with rollers or brushes

Area of use: Professional

Operating conditions

Substance concentration: n-butyl acetate content: ≥ 0 - $\leq 100\%$

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 480 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour). Effectiveness: 70%

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.

Exposure estimation: 2.7429 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.249351

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.

Exposure estimation: 145.1979 mg/m³

Risk Characterization Ratio (RCR): 0.483993

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra>

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC11: Non-industrial spray application

Area of use: Professional

Operating conditions

Substance concentration: n-butyl acetate content: ≥ 0 - $\leq 45\%$

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 480 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Minimize manual tasks.

Daily general cleaning of equipment and work area.

Regular inspection and maintenance of equipment and machinery.

Ensure that the activity is performed outside the operator's respiratory zone (head-product distance greater than 1m).

Avoid frequent and direct contact with the substance.

Check that risk reduction measures are implemented and that the conditions of use are respected.

Avoid splashes.

Make sure the spray booth is used.

Wear suitable clothing.

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.

Exposure estimation: 10.7143 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.974026

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.

Exposure estimation: 0.0001 mg/m³

Risk Characterization Ratio (RCR): 0.000001

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra> Please note that a revised version was used (see exposure estimates).

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC11: Non-industrial spray application

Area of use: Professional

Operating conditions

Substance concentration: n-butyl acetate content: ≥ 0 - $\leq 45\%$

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 480 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Minimize manual tasks.

Avoid frequent and direct contact with the substance.

Check that risk reduction measures are implemented and that the conditions of use are respected.

Daily general cleaning of equipment and work area.

Regular control and maintenance of equipment and machinery.

Make sure doors and windows are open (general ventilation).

Avoid splashes.

Use an adequately effective local ventilation system.

Wear suitable clothing.

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker, modified version. The concentration of the substance has been considered using a linear approach. Worker - dermal, long-term - systemic.

Exposure estimation: 4.8214 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.438312

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker, modified version. Operator - inhalation, long-term - local.

Exposure estimation: 153 mg/m³

Risk Characterization Ratio (RCR): 0.51

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra> Please note that a revised version was used (see exposure estimates).

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC11: Non-industrial spray application

Area of use: Professional

Operating conditions

Substance concentration: n-butyl acetate content: ≥ 0 - $\leq 100\%$

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 480 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Minimize manual tasks.

Avoid frequent and direct contact with the substance.

Check that risk reduction measures are implemented and that the conditions of use are respected.

Daily general cleaning of equipment and work area.

Regular inspection and maintenance of equipment and machinery.

Avoid splashes.

Make sure doors and windows are open (general ventilation).

Wear a half face mask with a P2L filter or better.

Wear suitable clothing.

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker, modified version. The concentration of the substance has been considered using a linear approach. Worker - dermal, long-term - systemic.

Exposure estimation: 4.8214 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.438312

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker, modified version. Operator - inhalation, long-term - local.

Exposure estimation: 116 mg/m³

Risk Characterization Ratio (RCR): 0.386667

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra> Please note that a revised version was used (see exposure estimates).

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC13: Treatment of articles by dipping and pouring

Area of use: Professional

Operating conditions

Substance concentration: n-butyl acetate content: ≥0 - ≤100%

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 480 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour). Effectiveness: 70%

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.

Exposure estimation: 1.3714 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.124675

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.

Exposure estimation: 145.1979 mg/m³

Risk Characterization Ratio (RCR): 0.483993

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra>

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC19: Manual mixing with direct contact with the only use of personal protective equipment

Area of use: Professional

Operating conditions

Substance concentration: n-butyl acetate content: ≥0 - ≤100%

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 240 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Forced local ventilation: Effectiveness: 80%

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Ensure a good standard of general or controlled ventilation (no less than 3-5 air changes per hour). Effectiveness: 30%

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.

Exposure estimation: 8.4857 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.771429

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.

Exposure estimation: 67.759 mg/m³

Risk Characterization Ratio (RCR): 0.225863

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra>

EXPOSURE SCENARIO CONSIDERED

Covered use descriptors: PROC19: Manual mixing with direct contact with the only use of personal protective equipment

Area of use: Professional

Operating conditions

Substance concentration: n-butyl acetate content: ≥ 0 - $\leq 100\%$

Physical state: liquid

Vapor pressure of the substance during use: 1120Pa

Process temperature: 20°C

Duration and frequency of application: 60 mins. 5 days a week

Indoor/Outdoor: Internal use

Risk management measures

Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour). Effectiveness: 70%

Wear chemically resistant gloves in combination with "basic" employee training. Effectiveness: 90%

Exposure estimation and reference to its source

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Worker - dermal, long-term - systemic.

Exposure estimation: 2.8286 mg/kg/day (body weight)

Risk Characterization Ratio (RCR): 0.257143

Evaluation method: EASY TRA v4.1, ECETOC TRA v3.0, Worker. Operator - inhalation, long-term - local.

Exposure estimation: 145.1979 mg/m³

Risk Characterization Ratio (RCR): 0.483993

Guidance for downstream users

For a comparison term, visit <http://www.ecetoc.org/tra>